

Contactless Temperature Screening Solutions



Dialog Enterprise brings you Contactless Temperature Screening Solutions, with all options including the basic feature of reading the temperature of employees, customers and visitors as they enter a building or a defined area. The system can also help identify the details and images of those who enter the defined location without wearing masks and detect the visitors whose temperature exceeds a pre-defined temperature threshold.



The Contactless Temperature Screening solution can be widely applied across multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campuses, customs, airports and hospitals for inspection and quarantine. **This is a must-have system for organizations which are grappling to find a solution to ensure workplace and occupational safety in the Post-Covid19 period.**

Benefits



Non-contact measurement to avoid physical contact



One second to detect skin-surface temperature of a person



Multi-person detection simultaneously



AI detection to reduce false alarms from other heat sources



Immediate alarm to notify operators

Features



Abnormal Temperature Detection



Accuracy $\leq 0.3^{\circ}\text{C}$



Large-area Screening
Real-time Monitoring



Fast Screening



Automatic Alarm



Simple Usage



Social Distancing

Basic

Body Temperature and Mask Detection

Device Make & Model
Hikvision | DS-K5671-3XF/ZU

After Sales Support and Service:
Enterprise Business Grade (24 x 7)

2 Years
Warranty



- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens
- Max.50,000 faces capacity
- Verification methods: Supports fast temperature measurement and face recognition with fever screening
- Authentication distance: 0.3-2 m
- Temperature range: 30-45°C
- Temperature accuracy: $\pm 0.5^{\circ}\text{C}$
- Supports 6 attendance statuses, including check in, check out, break in, break out, overtime in, overtime out
- Face recognition duration(1:N) $\leq 0.2\text{s}$
- Mask detection: Supports face mask wearing alert and forced mask wearing alert

Standard

Temperature Screening Thermographic Handheld Camera

Device Make & Model
Hikvision | DS-2TP21B-6AVF/W

After Sales Support and Service:
Enterprise Business Grade (24 x 7)

2 Years
Warranty



- 160 × 120 resolution (thermal), and 8 MP resolution (optical)
- Thermographic accuracy up to $\pm 0.5^{\circ}\text{C}$
- Display fusion of thermal view and optical view
- 640 × 480 resolution 3.5" LCD touch display
- Support live view on PC, mobile device or external monitor
- Support audio intercom
- Support color highlight alarm and audio alarm

Advanced

Temperature Screening Thermographic Bullet Camera

Device Make & Model
Hikvision Thermal Camera | DS-2TD2617B-6/PA
Hikvision Black Body Calibrator | DS-2TE127-G4A
Hikvision NVR with 2TB HDD | DS-7732NI-I4
Hikvision POE Switch | DS-3E0105P-E
Hikvision Tripod (2) | DS-2907ZJ
Hikvision Tripod Adapter (2) | DS-2909ZJ

After Sales Support and Service:
Enterprise Business Grade (24 x 7)

2 Years
Warranty



- 160 × 120 resolution in thermal channel, high sensitivity sensor
- Temperature range: 30-45°C
- Temperature accuracy: $\pm 0.5^{\circ}\text{C}$
- Reliable temperature exception alarm function
- 3D DNR, image detail enhancement
- Audio alarm

Premium

Temperature Screening Thermographic Bullet Camera

Device Make & Model
Hikvision Thermal Camera | DS-2TD2636B-15/P
Hikvision Black Body Calibrator | DS-2TE127-G4A
Hikvision NVR with 2TB HDD | DS-7732NI-I4
Hikvision POE Switch | DS-3E0105P-E
Hikvision Tripod (2) | DS-2907ZJ
Hikvision Tripod Adapter (2) | DS-2909ZJ

After Sales Support and Service:
Enterprise Business Grade (24 x 7)

2 Years
Warranty



- 384 × 288 high resolution in thermal channel, high sensitivity sensor
- Temperature range: 30-45°C
- Temperature accuracy: $\pm 0.5^{\circ}\text{C}$
- Reliable temperature exception alarm function
- 3D DNR, image detail enhancement
- 4MP resolution in optical channel

